

C9P: PLL LVPECL SERIES: ULTRA HF CLOCK OSCILLATOR, LVPECL, +3.3 VDC

DESCRIPTION: A crystal controlled, high frequency, highly stable oscillator, adhering to Low Voltage Differential Signaling (LVPECL) Standards. The output can be Tri-stated to facilitate testing or combined multiple clocks. The device is contained in a sub-miniature, very low profile, leadless ceramic SMD package with 6 gold contact pads. This miniature oscillator is ideal for today's automated assembly environments.

APPLICATIONS AND FEATURES:

- Infiniband; Fiber Channel; SATA; 10GbE; Network Processors; SOHO Routing; Switches;
- Common Frequencies: 150 MHz; 156.25 MHz; 155.52 MHz; 161.1328 MHz; 212.5MHz; 312.5MHz
- +3.3 VDC LVPECL
- Frequency Range from 750KHz to 800 MHz
- PLL multiplication (F>25MHz)
- Miniature Ceramic SMD Package Available on Tape and Reel
- Lead Free and ROHS Compliant

■ ABSOLUTE MAXIMUM RATINGS:

PARAMETER	SYMBOL	VALUE	UNIT
Operating temperature range	Ta	-40...+85	°C
Storage temperature range	T(stg)	-55...+90	°C
Supply voltage	Vcc	+4.6	VDC
Maximum Input Voltage	Vi	Vss-0.5...Vcc+0.5	VDC
Maximum Output Voltage	Vo	Vss-0.5...Vcc+0.5	VDC

■ ELECTRICAL PARAMETERS:

PARAMETER	SYMBOL	TEST CONDITIONS ¹	VALUE	UNIT	
Nominal Frequency	fo		0.75~ 800.00**	MHz	
Supply Voltage	Vcc		+3.3 ±5%	VDC	
Supply Current	Is		100.0 MAX	mA	
Output Logic Type			LVPECL		
Load		Connected between each output and Vcc – 2.0 VDC	50	Ω	
Output Voltage Levels	Voh Vol	min max	Vcc-1.025 Vcc-1.620	VDC VDC	
Duty Cycle	DC	Measured at 50% of Vcc	40/60 to 60/40 or 45/55 to 55/45	%	
Rise / Fall Time	tr / tf	Measured at 20/80% and 80/20% Vcc Levels	0.7 TYP 1.0 MAX ²	ns	
Jitter	J	Integrated Phase t _{ji} RMS, F _j = 12 kHz...20 MHz ⁵	Fo=155.52MHz	2.6 TYP**	ps
			Fo=622.08MHz	2.5 TYP**	
		Random period Jitter R _j using wavecrest analyzer ⁴	Fo=155.52MHz.	4 TYP **	ps
			Fo=622.08MHz	6 TYP **	
Acumm. Peak to Peak Jitter Tp-p using wavecrest analyzer ⁴		Fo=155.52MHz.	30 TYP**	ps	
		Fo=622.08MHz	40 TYP**		
Phase Noise	£(Δf)	typ. @155.52MHz ⁶	Δf=10 Hz	-60	dBc/Hz dBc/Hz dBc/Hz dBc/Hz dBc/Hz dBc/Hz
			Δf=100 Hz	-90	
			Δf=1 KHz	-120	
			Δf=10 KHz	-125	
			Δf=100 KHz	-121	
			Δf=1M Hz	-121	
			Δf=10M Hz	-140	
Δf≥20M Hz	-145				
Overall Frequency Stability	Δf/fc	Op. Temp., Aging, Load, Supply and Cal. Variations	±20, ±25, ±50, or ±100 MAX ³	ppm	
Enable High Option; Pin 1 Output Enabled Output Disabled	En Dis	High Voltage or No Connect Ground	0.7•Vcc MIN 0.3•Vcc MAX	VDC VDC	
Enable Low Option; Pin 1 Output Disabled Output Enabled	Dis En	High Voltage Ground or No Connect	0.7•Vcc MIN 0.3•Vcc MAX	VDC VDC	

- *1 Test Conditions Unless Stated Otherwise: Nominal Vcc, Nominal Load, +25 ±3°C
- *2 Frequency Dependent
- *3 Not All Stabilities Available With All Temperature Ranges—Please Consult Factory For Availability
- *4 Measured with Wavcrest SIA-3000A 10,000, Cycles no filtering
- *5 Calculated from Agilent 5500 phase noise measurements
- *6 Measured with Agilent 5500

■ **PART NUMBERING SYSTEM:**

SERIES	SYMMETRY	TEMPERATURE RANGE (°C)	FREQUENCY STABILITY (Overall)	FREQUENCY (MHz)	Enable/Disable
C9P: UHF +3.3Vdc Clock with LVPECL Comp. Output	A: 40/60 to 60/40% T: 45/55 to 55/45%	R: 0...+50 S: 0...+70 U: -20...+70 V: -40...+85**	K: ±20 ppm** L: ±25 ppm H: ±50 ppm J: ±100 ppm	0.75...800.000	Enable High – standard (Omit Suffix) EL; Enable Low

EXAMPLE: -155.520

Clock Oscillator, 7x5mm Package, +3.3 VDC Supply Voltage, LVPECL Output, Standard Symmetry, 0...+70°C Operating Temperature Range, ±50 ppm Total Frequency Stability, 155.520 MHz

** ±20ppm stability may not be available at all combinations, please consult the factory for any custom requirements.

■ **MECHANICAL PARAMETERS:**

OUTLINE TOLERANCE:
±0.006" / 0.15mm
(Unless otherwise specified)

PIN FUNCTIONS:
[1] ENABLE/ DISABLE
[2] NO CONNECT
[3] CASE GROUND
[4] OUTPUT
[5] COMP. OUTPUT
[6] SUPPLY VOLTAGE

MARKING:
C9PASH
155.52
R D/C

***0.01µF external by-pass filter is recommended as seen on solder pattern.**

SOLDER PATTERN

■ **REFLOW PROFILE:**

